

# NASA TECH BRIEF

## Marshall Space Flight Center



NASA Tech Briefs announce new technology derived from the U.S. space program. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

### Coherence-Length Extender

#### The problem:

To form a hologram of a large object, the laser sources used must produce beams that are intense and have the maximum possible coherence length. In general, the available laser sources cannot provide both at the same time. Therefore, holograms of large objects have been limited by the coherence and intensity capabilities of the available laser sources.


#### The solution:

Holograms of large objects may be formed by using several coherent low-intensity laser sources.

#### How it's done:

In holography, the maximum coherence length from any given laser source can be obtained by equating the lengths of the reference and object beams. The setup shown in the figure utilizes this principle with three beams. In each instance, the total length of the object beam is equal to the total length of its respective reference beam. There is sufficient overlap between the adjacent beams to produce uniform brightness over the entire object image.

The total number of object beams necessary to record the entire object is determined by the dimension



(continued overleaf)

of the object and the coherence length of each laser source. Here the coherence length of each source is just sufficient to record one section of the object, labeled d. As shown, three sources are necessary to record the entire object.

It is noted that each separate reference beam is incident on the film at a different angle. Therefore, on reconstruction with a single reference beam, the plate must be rotated back and forth through some small angle,  $\delta$ , where

$$\delta = \alpha + \beta + \gamma$$

where  $\alpha$ ,  $\beta$ , and  $\gamma$  were the original angles associated with the three reference beams used for construction of the hologram.

If several low intensity laser sources are available, they can be applied simultaneously by a method similar to that in the figure. Each laser source is then used to establish one object beam and one reference beam whose

path lengths are equal, recording a small portion of the total object. When used in this fashion, the drift between the lasers is inconsequential since the object beam from the first source interferes only with the reference beam from the second, and so on.

**Note:**

Requests for further information may be directed to:  
Technology Utilization Officer  
Marshall Space Flight Center  
Code A&PS-TU  
Marshall Space Flight Center, Alabama 35812  
Reference: B73-10399

**Patent status:**

NASA has decided not to apply for a patent.

Source: R. L. Kurtz  
Marshall Space Flight Center  
(MFS-22434)